

**KOSTRZEWA®**  
Experts in heating

established in 1978

## Compact Bio Luxury

Device with a look you  
will never get tired of.

Demonstration of strength and independence

models [kW]

16 24



Broadband 6-wire  
lambda probe



ecoburning

Compact Bio Luxury boilers meet the  
requirements of PN - EN 303-5:2012 standard.



App Store



Google play

Applikation  
iOS

Applikation  
Android


fuels



pellet



pellet/oats  
50 / 50



wood



automatic

7/24

factory  
service

> 91%

boiler  
efficiency

5 class

boiler class

5 year

5 year warranty  
+ 2 years  
extension



GSM  
module



INTERNET  
module

## Boiler description

Compact Bio Luxury is a device with a look that you will never get tired of and that will become an inspiration for the competition. This is a compact body with very small dimensions made of aesthetically profiled sheets painted with a light green structural powder lacquer. In combination with silver galvanised elements, such as the tank, this gives the device the character and lightness. The constructors from Kostrzewa company created the device bearing in mind the use of wood and granulated biomass.

There aim was to guarantee easy operation, low fuel consumption, and small overall dimensions provided for very small boiler rooms, as well as high functionality.

The device is comprised of four connected elements:

1. Boiler body – made in 3T (time, turbulator, temperature) technology

2. Proved solution – Platinum Bio burner, which automatically combusts pellet and oats.
3. Platinum Bio automatics, the task of which is temperature adjustment of one heating circuit + hot tap water. Innovative flame and temperature Fuzzy Logic 2 generation adjustment has been applied.
4. Large tank made of galvanised sheet to additionally secure the tank against corrosion during operation in difficult conditions.

1. Fuzzy Logic 2 generation method saves up to 20% fuel
2. Lambda probe saves up to 20% fuel.



- 1 **Platinum Bio Slim driver** is a modern microprocessor chip, which controls not only the boiler but also the central heating system and the system of hot tap water. Power of the blower is smoothly regulated by Fuzzy Logic 2 generation method.
- 2 **Loading chamber** – large loading chamber extending the time of single fuel charge combustion.
- 3 **Ceramic chamber** – increases the temperature of burning process to 900°C and with the participation of primary and secondary air it burns down left gases thus increasing the efficiency of the device.
- 4 **Platinum Bio burner** – auto-cleaning, innovative, gravitational burner with Fuzzy Logic 2 generation modulation.
- 5 **Tank**
- 6 **Special thermal insulation of the device**
- 7 **Broadband lambda probe<sup>2</sup>**

# Compact Bio Luxury

- delivery to your home or to the construction site
- guarantee and post-guarantee service
- 5-year guarantee with the option to prolong it for 2 years
- network of service staff
- distribution network for devices and spare parts




1 litre of oil = 2 kg of pellet



## Multi-fuel functionality

In automatic fuel feeding mode it uses pellet and oats – in manual fuel feeding it burns wood and chips.



## Platinum Bio Burner

Energy-efficient engine of the whole system  
Mechanically and technically advanced element responsible for production of thermal energy from pellet. Durable, energy-efficient, reliable, quiet – made of heat-resistant and acid-resistant steel allows continuous and reliable operation for many years.



## Platinum Bio Slim 2 generation Fuzzy Logic automatics

**Super comfort** – control over the whole system. Automatics was designed to control more devices in your boiler room.

Smoothly and intelligently it adjusts fuel and air dose. It was created to collaborate with boilers combusting pellet, oats, pea coal and wood.

- **Ecology** – CO<sub>2</sub> emission = 0
- **Cost-efficiency** – 2 generation Fuzzy Logic modulation of flame saves up to 20% fuel. The whole system of boiler room control is based on **soft steering** depending on the energy requirement in respective storeys of building or hot tap water requirement. Automatically and precisely it doses the amount of air needed for combustion, **saving up to 40% fuel**.
- **Economy** Platinum Bio Burner – energy-efficient engine of the whole system.
- **Innovativeness** – the exchanger construction according to 3T definition. Thanks to application of 3T method (time, turbulator, temperature) we created an exchanger with very small dimensions and high efficiency.
- **Multi-functionality** – the device is able to control several heating circuits, solar system and buffer tank – option.
- **Safety** – MAP sensor – option
- **Comfort** – the device is fully automated – it lights up and puts itself out automatically
- **Durability** – 5 years warranty.

The device is constructed for pellet and oats combustion. Biomass combustion does not emit harmful gases to atmosphere, as opposed to combustion of coal or oil. By selecting renewable fuel every one may contribute to the fight against climate changes. The device is made of high quality materials and additionally covered by 3-year warranty, which lowers the cost of operation and increases confidence in new technology.

**2 generation Fuzzy Logic adjustment method reduces the amount of fuel combusted to 20% as well as reduces wear of subassemblies, as compared with burners made by competition.**

The main advantage of the burner is its simple operation based on pouring fuel into the main tank and pressing START. Within a few minutes the device will automatically light up and it will tend to keep constant temperature in rooms and constant temperature of hot tap water. Fuel tank is made of galvanised sheet – zinc coating of the sheet limits the corrosion of fuel tank. If you want to use wood – it is enough to set the wood option in the menu in central heating boiler with a fan – burner will automatically switch off, and fan will start operation.

- Automatic burner
- flame control by means of a photocell
- low heat inertia during start and stop
- low electricity consumption
- possibility to control up to 16 heating circuits (heaters and floor heating or hot tap water) – option
- control of the burner's working temperature – ensures security on the highest level.
- 3 phases of fuel lighting up eliminate gas explosions during lighting up
- AUTOSTART function after blackouts – restoring last settings
- air division into primary and secondary – reduces CO<sub>2</sub> emission to the level of emission from gas and oil burners
- auto-cleaning function, automatically removes deposit from burner grid – function is not present in gravitational burners
- oats – burner construction enables corn (oats) combustion<sup>2</sup>
- Statistics – the function allows, for instance, the review of minimum, maximum and average power of a burner, minimum and maximum, as well as average fuel consumption
- Temperature parameters are presented as digits and graphs on a big graphic display, and many more useful functions – (option).
- cooperation with GSM module
- cooperation with INTERNET module.

1. 2 generation Fuzzy Logic method saves up to 20% fuel  
2. recommended pellet/oats mix to be kept in 50/50 proportion

Detailed technical data of the device are available from the manufacturer or distributor.  
The manufacturer reserves the right to construction changes of the boiler, which improve the device functioning. Selection of power to the device was made for 4th climate zone of Poland (max. temperature: 24 °C).

| Type                   | CB 16    | CB 24     |
|------------------------|----------|-----------|
| building area [sqm]    | 50 - 200 | 100 - 300 |
| nominal power [kW]     | 16       | 24        |
| depth [mm]             | 790      | 790       |
| width [mm]             | 1175     | 1277      |
| height [mm]            | 1370     | 1370      |
| fuel tank capacity [L] | 208      | 208       |
| stack diameter [mm]    | 160      | 160       |



Distributor:



**Boiler-Gas.ru**

Перейти на сайт