

Innovation + Quality

## Thermostats "vindo TH" and "vindo TD"

Product range













The thermostats "vindo TH" (connection thread M  $30 \times 1.5$ ) and "vindo TD" (squeeze connection) with liquid sensor serve to control the room temperature.

The thermostats with their new, slim design and reduced dimensions combine exclusive form with high functional efficiency.

The operation and optical display are excellent. The nominal values are easily set. Where there is insufficient lighting or for visually handicapped persons, the basic setting "3" can be easily found with the help of the tactile setting devices.

The thermostat is elegant due to its balanced forms. The lines are clear and smooth.

The collar nut of the "vindo TH" is nickel plated and that of the "vindo TD" is made of white plastic, RAL 9016.

The handgrip is white (RAL 9016), the lower central piece is black.

	Item	Packing unit	Item no.	Information
	Thermostat "vindo тн" with liquid sensor Connection thread M 30 x 1.5			Max. heating water temperature: 120°C.
- \$ · · · \$ · · · \$ - · · · · · · · · ·	white model	(10)	101 30 66	With '0' setting, temperature range 7-28°C graduation on cap 0 <b>★</b> 1-5
- \$\dots \cdot \cd	Thermostat "vindo TD" with liquid sensor Squeeze connection white model	(10)	101 30 76	With '0' setting, temperature range 7-28°C graduation on cap 0 <b>☆</b> 1-5

Further information can be found in the Oventrop catalogue "Products" and on the internet, product range 1



OVENTROP GmbH & Co. KG Paul-Oventrop-Straße 1 D-59939 Olsberg Germany

Germany
Telephone +49 (0) 29 62 82-0
Telefax +49 (0) 29 62 82-450
E-Mail mail@oventrop.de
Internet www.oventrop.de

Product range 1 PR 235-1/2/04.2011/DD Edition 2011