

ONE APPLIANCE – ENDLESS POSSIBILITIES

The SH SL(i) is the only oversink unit in STIEBEL ELTRON's small water heater range that can supply multiple draw-off points with hot water simultaneously. It is also an alternative DHW option when there is insufficient room under the washbasin.

Any tap will suit – plus outstanding quality

In contrast to other small water heaters, the sealed unvented SH SL(i) oversink unit can be combined with most pressure taps, providing you with the ultimate in DHW convenience.

Benefits for your home

- › Infinitely variable temperature selection from 35 °C to 82 °C on the appliance
- › Temperature limit as anti-scalding protection
- › Energy saving mode
- › Extremely large amount of mixed water
- › Multiple draw-off points

SH SL(i)



Model	PLUS		
	SH 10 SLi	SH 15 SLi	SH 15 SL 3.3 kW
	229476	229478	229479
Energy efficiency class	A	A	A
Rated capacity	l 10	15	15
Mixed water volume at 40 °C	l 19	28	28
Max. throughput	l/min 10	12	12
Connected load from/to	kW 2		3.3
Power supply	-/V/Hz 1/N/PE/230/50/60	1/N/PE/230/50/60	1/N/PE/230/50/60
Available temperature range	°C ca. 35 - 82	ca. 35 - 82	ca. 35 - 82
Standby energy consumption/			
24 h at 65 °C	kWh 0.34	0.4	0.4
Height/Width/Depth	mm 503/295/275	601/316/295	601/316/295