



As the standard model, the SHW ACE floorstanding cylinder is an exceptionally economical, yet powerful, hot water solution for the whole house, because it can supply hot water to multiple draw-off points.

Robust and reliable

All models, from the standard version up, feature a solid steel tank with a special enamel coating on the inside – for a long service life.

Benefits for your home

-) Rapid heat-up key
- Easy to maintain due to protective anode with consumption indicator
- > Thermometer for operational monitoring

SHW 200 ACE

		TREND		
Model		SHW 200 ACE	SHW 300 ACE	SHW 400 ACE
		070074	070075	070076
Energy efficiency class		С	С	С
Rated capacity	1	200	300	400
Mixed water volume at 40 °C	1	392	582	768
Max. throughput	I/min	30	38	45
Connected load from/to	kW	2-6	2-6	2-6
Connected load with ~ 230 V	kW	2-6	2-6	2-6
Connected load with ~ 400 V	kW	4-6	4-6	4-6
Power supply	-/	1/N/PE, 2/N/PE,	1/N/PE, 2/N/PE,	1/N/PE, 2/N/PE,
	V/	3/PE/230/400/	3/PE/230/400/	3/PE/230/400/
	Hz	50/60	50/60	50/60
Available temperature range	°C	35-82	35-82	35-82
Standby energy				
consumption/24 h at 65 °C	kWh	1.9	2.3	2.6
Height/Width/Depth	mm	1578/550/690	1593/650/790	1763/700/840
·		· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	

