

SHW S

COMPELLING EFFICIENCY – IMPRESSIVE DHW CONVENIENCE

The SHW S floorstanding DHW cylinder offers an exclusive level of convenience – even when retrofitted – thus enhancing any home. Its capacity is ideal for detached houses.

Well insulated

Highly effective thermal insulation keeps heat dissipation to a minimum. This makes the SHW S one of the most efficient appliances of its type.

Benefits for your home

- › Rapid heat-up key
- › Comprehensive standard equipment level
- › Low standby energy consumption

Model	PLUS				
	SHW 300 WS	SHW 400 WS	SHW 200 S	SHW 300 S	SHW 400 S
	185352	185353	182120	182121	182122
Energy efficiency class	C	C	C	C	C
Rated capacity	l 300	400	200	300	400
Mixed water volume at 40 °C	l 553	740	392	582	768
Max. throughput	l/min 38	45	30	38	45
Connected load from/to	kW 2-6	2-6	2-6	2-6	2-6
Connected load with ~ 230 V	kW 2-4	2-4	2-4	2-4	2-4
Connected load with ~ 400 V	kW 2-6	2-6	2-6	2-6	2-6
Power supply	1/N/PE, 3/N/PE/ -/V/Hz 230/400/50/60	1/N/PE, 3/N/PE/ 230/400/50/60	1/N/PE, 3/N/PE/ 230/400/50/60	1/N/PE, 3/N/PE/ 230/400/50/60	1/N/PE, 3/N/PE/ 230/400/50/60
Available temperature range	°C 35-82	35-82	35-82	35-82	35-82
Standby energy consumption/24 h at 65 °C	kWh 1.8	2.1	1.4	1.8	2.1
Height/Width/Depth	mm 1593/700/815	1763/750/865	1578/630/730	1593/700/815	1763/750/865

