

SHZ LCD

GREATER CONVENIENCE – LESS ENERGY

The electronically controlled SHZ LCD wall mounted water heater excels on efficiency – with energy efficiency label A at 30 l nominal capacity. Three ECO programs mean that energy saving and DHW heating can be adjusted to accurately reflect actual requirements.

Everything at a glance

In ECO DYNAMIC learning mode, the energy saving options are automatically adjusted according to the individual draw-off pattern. The selected program and the amount of available water can be checked on the backlit display at any time.



Benefits for your home

- › Variable and precise temperature settings from 20 °C to 85 °C
- › Efficient operation thanks to three automatic ECO functions
- › Special enamel coating for a long service life



Model	SHZ 30 LCD	SHZ 50 LCD	SHZ 80 LCD	SHZ 100 LCD	SHZ 120 LCD	SHZ 150 LCD
	231251	231252	231253	231254	231255	231256
Energy efficiency class	A	B	B	C	C	C
Nominal capacity	l 30	50	80	100	120	150
Mixed water volume at 40 °C	l 59	97	159	198	235	292
Max. flow rate	l/min 18	18	18	18	18	18
Connected load from/to	kW 1-6	1-6	1-6	1-6	1-6	1-6
Connected load ~ 230 V	kW 1-4	1-4	1-4	1-4	1-4	1-4
Connected load ~ 400 V	kW 1-6	1-6	1-6	1-6	1-6	1-6
Power supply	-/ 1/N/PE, 2/N/PE, 3/N/PE/ V/ 230/400/ Hz 50/-	1/N/PE, 2/N/PE, 3/N/PE/ 230/400/ 50/-	1/N/PE, 2/N/PE, 3/N/PE/ 230/400/ 50/-	1/N/PE, 2/N/PE, 3/N/PE/ 230/400/ 50/-	1/N/PE, 2/N/PE, 3/N/PE/ 230/400/ 50/-	1/N/PE, 2/N/PE, 3/N/PE/ 230/400/ 50/-
Temperature setting range	°C 20-85	20-85	20-85	20-85	20-85	20-85
Standby energy consumption/ 24 h at 65 °C	kWh 0.46	0.54	0.67	0.86	0.99	1.1
Height	mm 770	740	1050	1050	1210	1445
Width	mm 410	510	510	510	510	510
Depth	mm 420	510	510	510	510	510



Boiler-Gas.ru
Перейти на сайт

