



The Clear Choice
Water Filtration Systems

www.aquafilter.com

FCPP

PP Yarn Sediment Filter Cartridge



Made in EU

General Description:

AQUAFILTER FCPP series cartridges are made of FDA-approved polypropylene string wound on a polypropylene core which strengthens the cartridge.



It has a broad chemical compatibility, good temperature resistance and low cost. **FCPP** series cartridges are primarily used as the first stage of filtration of cold potable water.

Cartridges are characterized by excellent sediment absorption of sand, silt, rust and suspended solids from potable water. In addition, these filter cartridges effectively protect expensive home appliances and residential plumbing systems.

Features:

- Competitive Pricing
- FDA CFR Title 21 Compliance
- Removal ratings from 1 to 100 micron
- 87% efficiency at stated nominal micron rating
- Consistently efficient filters
- Provides excellent filtration with low inlet pressure
- Provides first stage filtration for potable water*
- Chemical resistant
- Prevents development of microorganisms
- Made in the EU with High Quality materials

* in case of filter cartridge with 20µm and higher.





The Clear Choice
Water Filtration Systems

www.aquafilter.com

FCPP

PP Yarn Sediment Filter Cartridge


CAT #	SIZE	Micron	Weight Jar	Max. Flow		Filter life*		
				lpm	gpm	liters	galons	months
FCPP1	9 7/8" x 2 1/2" 252 mm (+/- 2 mm) x 57 mm (+/- 2 mm)	1 µm	120 g (+/- 5 g)	20	5.29	12,000	3,170	3 - 6
FCPP5	9 7/8" x 2 1/2" 252 mm (+/- 2 mm) x 57 mm (+/- 2 mm)	5 µm	120 g (+/- 5 g)	20	5.29	12,000	3,170	3 - 6
FCPP10	9 7/8" x 2 1/2" 252 mm (+/- 2 mm) x 57 mm (+/- 2 mm)	10 µm	120 g (+/- 5 g)	20	5.29	12,000	3,170	3 - 6
FCPP20	9 7/8" x 2 1/2" 252 mm (+/- 2 mm) x 57 mm (+/- 2 mm)	20 µm	120 g (+/- 5 g)	20	5.29	12,000	3,170	3 - 6
FCPP50	9 7/8" x 2 1/2" 252 mm (+/- 2 mm) x 57 mm (+/- 2 mm)	50 µm	120 g (+/- 5 g)	20	5.29	12,000	3,170	3 - 6
FCPP100	9 7/8" x 2 1/2" 252 mm (+/- 2 mm) x 57 mm (+/- 2 mm)	100 µm	120 g (+/- 5 g)	20	5.29	12,000	3,170	3 - 6
FCPP1-L	20" x 2 1/2" 510 mm (+/- 5 mm) x 57 mm (+/- 2 mm)	1 µm	245 g (+/- 5 g)	30	7.09	16,000	4,220	3 - 6
FCPP5-L	20" x 2 1/2" 510 mm (+/- 5 mm) x 57 mm (+/- 2 mm)	5 µm	245 g (+/- 5 g)	30	7.09	16,000	4,220	3 - 6
FCPP10-L	20" x 2 1/2" 510 mm (+/- 5 mm) x 57 mm (+/- 2 mm)	10 µm	245 g (+/- 5 g)	30	7.09	16,000	4,220	3 - 6
FCPP20-L	20" x 2 1/2" 510 mm (+/- 5 mm) x 57 mm (+/- 2 mm)	20 µm	245 g (+/- 5 g)	30	7.09	16,000	4,220	3 - 6
FCPP50-L	20" x 2 1/2" 510 mm (+/- 5 mm) x 57 mm (+/- 2 mm)	50 µm	245 g (+/- 5 g)	30	7.09	16,000	4,220	3 - 6
FCPP100-L	20" x 2 1/2" 510 mm (+/- 5 mm) x 57 mm (+/- 2 mm)	100 µm	245 g (+/- 5 g)	30	7.09	16,000	4,220	3 - 6
FCPP5M10B	9 7/8" x 4 1/2" 252 mm (+/- 2 mm) x 100 mm (+/- 2 mm)	5 µm	425 g (+/- 5 g)	40	10.58	18,000	4,755	3 - 6
FCPP20M10B	9 7/8" x 4 1/2" 252 mm (+/- 2 mm) x 100 mm (+/- 2 mm)	20 µm	425 g (+/- 5 g)	40	10.58	18,000	4,755	3 - 6
FCPP5M20B	20" x 4 1/2" 510 mm (+/- 5 mm) x 100 mm (+/- 2 mm)	5 µm	895 g (+/- 5 g)	60	21.16	24,000	6,340	3 - 6
FCPP20M20B	20" x 4 1/2" 510 mm (+/- 5 mm) x 100 mm (+/- 2 mm)	20 µm	895 g (+/- 5 g)	60	21.16	24,000	6,340	3 - 6

* filter cartridge lifetime depends on contamination level of potable water.

Specifications:

Filter media: PP
Core: PP or PET
Nominal micron rating: 1, 5, 10, 20, 50, 100
Min. feedwater temp. 2°C (35°F)
Max. feedwater temp. 65°C (149°F)
Lengths: 10", 20"
Outer diameter: 2 1/2", 4 1/2"
Inner diameter: 1, 1"
Avg. Efficiency: 90%

Inner diameter: 1, 1"



Aquafilter Manufacturing Facility



Aquafilter Inc.
Hunt Valley 21030, USA
us@aquafilter.com




Aquafilter Germany
15234 Frankfurt, Germany
de@aquafilter.com




Aquafilter Europe
91-222 Lodz, Poland
pl@aquafilter.com




Pressure drop diagram for 10" cartridges



Pressure drop diagram for 20" cartridges



Pressure drop diagram for 10", 20" Big Blue®



Polypropylene yarn nominal rating sediment filter cartridge available in 10", 10" Big Blue®, 20" and 20" Big Blue® size and 1, 5, 10, 20, 50, 100 micron rating. Generally used with all standard size filter housings. Low cost pre-filtration.

IMPORTANT NOTICE: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. We recommend regularly scheduled maintenance and replacement of the filter cartridge in order for the product to perform properly. Improper installation and maintenance may result in property damage due to water leakage.
Limited Warranty: AQUAFILTER warrants that this product is free from defects in materials and workmanship. This limited warranty does not apply to failures that result from abuse, misuse, alteration or failure to properly comply with installation or cartridge change instructions.

All Aquafilter images, trademarks, logos, and other intellectual property are the sole and exclusive property of Aquafilter, Inc. and may not be used without our express written permission.

